

## **Technical Data Sheet**


Aluminium Stair Nosing W65mm x H10mm x T3mm with corduroy finish


## PRODUCT DESCRIPTION

Aluminium stair nosing with non-slip corduroy finish. Offers high slip resistance and is suitable for all stable indoor and outdoor substrates. It has been specifically designed to to comply with the requirements of AS 1428.1 - 2009.

Material	
Colour	
Finish	

Aluminium Alloy - Hard Anodised
Black/Clear
Corduroy





## Slip Resistance Testing

See Australian Standards Hand Book 198: 2014 (HB 198), "An Introductory Guide to Slip Resistance of Pedestrian Materials" in order to determine a classification of a slip resistance rating. This document outlines the minimum ratings of location and situation of a pedestrian surface.

TEST	AS/NZS 4586:2004 Appendix A
TYPE	Wet Pendulum Test
RATING	Four S slider Mean BPN = 78 Class = P5
TEST	AS/NZS 4586:2004 Appendix D
TYPE	OIL-WET Ramp
RATING	Mean overall acceptance angle = 35 ° Class R13

## **Luminance Testing**

Compliance for Luminance contrast varies with colour tactile and the substrate onto which you wish to have them installed. Certification of compliance would require testing of the tactile on your surface.

E: sales@safespot.com.au